

YOUR DETAILS

Name: _____ Company Name: _____
 Address: _____
 Tel: _____ Fax: _____
 E-mail: _____ Your Reference: _____

GENERAL NOTES : Rods & Mortar can be used internally and externally for straight and curved glass block walls. For 60/15 or 120/30 fire rated walls please contact Glass Block Technology on the number above.

GLASS BLOCK STYLE

PANEL DIMENSIONS

NOTE : IF A SINGLE DIMENSION EXCEEDS 6m, AN INTERMEDIATE SUPPORT OR SLIP EXPANSION JOINT SHOULD BE INCORPORATED.

	NAME/TYPE ie FLEMISH	SIZE ie 190X190X80mm	CLEAR/COLOURED ie COBALT BLUE	Nº. BLOCKS HIGH	X	Nº. BLOCKS WIDE	Nº. OF PANELS	ALTERNATIVELY GIVE FULL PANEL DIMENSIONS	
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	X	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	X	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	X	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	X	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	X	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

SAFEWALL (COMPLETE AS REQ'D)

NOTE : FOR BEST INTEGRAL STRENGTH, GLASS BLOCK PANELS SHOULD BE INSTALLED INTO A FOUR-SIDED OPENING.

END POSTS

NO. OF POSTS REQ'D : FINISH : WHITE SILVER GREY END BOSS : POLISHED BRUSHED SATIN

CORNER POSTS

NO. OF POSTS REQ'D : FINISH : WHITE SILVER GREY CORNER BOSS : POLISHED BRUSHED SATIN

A PAIR OF BOSS SECTIONS IS REQUIRED PER POST USED

DRAWINGS

Sketch layout as required :

CURVED PANELS

FIRE RATING

SPECIALIST GLASS BLOCKS (PLEASE SUPPLY SKETCH)

IF CONSTRUCTING CURVED WALL, PLEASE GIVE INTERNAL RADIUS DIMENSION :

ARE ANY OF THE PANELS FIRE RATED?
 LINE 1 2 3 4 5
 G60/F15 G120/F30

INDICATE STYLE AND NO. OF BLOCKS REQUIRED :

END DOUBLE END
 CORNER RADIUS

NOTE : GLASS BLOCK TECHNOLOGY RODS & MORTAR QUOTATIONS ARE BASED ON USING 10mm JOINTS.

SPECIAL CIRCUMSTANCES/COMMENTS

DESPATCH DETAILS PLEASE STATE DELIVERY ADDRESS IF DIFFERENT FROM ABOVE:

SPECIFY DELIVERY SERVICE (TICK AS REQUIRED) : 3 TO 5 DAY ECONOMY OVERNIGHT

OVERNIGHT CARRIAGE IS SUBJECT TO A SURCHARGE.