

EASIFIX

INSTALLATION SYSTEM

QUOTATION

**ON COMPLETION PLEASE
FAX TO 0161 285 1503**

YOUR DETAILS

Name: _____ Company Name: _____
 Address: _____
 Tel: _____ Fax: _____
 E-mail: _____ Your Reference: _____

GLASSBLOCK
 TECHNOLOGY

SALES OFFICE : 170 Lodge Lane, Hyde, Cheshire SK14 4LB
 TEL : 0161 612 6893 FAX : 0161 285 1503
 WEB : www.glassblocks.co.uk
 E-MAIL : info@glassblocks.co.uk

GENERAL NOTES : Easifix is recommended for internal use only • Maximum panel size 9m² • Easifix can only be used for constructing straight glass block walls • Easifix installation method carries no fire rating.

GLASS BLOCK STYLE

PANEL DIMENSIONS

NOTE : ONLY 80mm WIDE GLASS BLOCKS CAN BE USED IN CONJUNCTION WITH EASIFIX

NAME/TYPE ie FLEMISH	SIZE ie 190X190X80mm	CLEAR/COLOURED ie COBALT BLUE	Nº. BLOCKS HIGH	X	Nº. BLOCKS WIDE	Nº. OF PANELS	ALTERNATIVELY GIVE FULL PANEL DIMENSIONS
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	X	<input type="text"/>	<input type="text"/>	<input type="text"/> mm HIGH X <input type="text"/> mm WIDE
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	X	<input type="text"/>	<input type="text"/>	<input type="text"/> mm HIGH X <input type="text"/> mm WIDE
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	X	<input type="text"/>	<input type="text"/>	<input type="text"/> mm HIGH X <input type="text"/> mm WIDE
4	<input type="text"/>	<input type="text"/>	<input type="text"/>	X	<input type="text"/>	<input type="text"/>	<input type="text"/> mm HIGH X <input type="text"/> mm WIDE
5	<input type="text"/>	<input type="text"/>	<input type="text"/>	X	<input type="text"/>	<input type="text"/>	<input type="text"/> mm HIGH X <input type="text"/> mm WIDE

EASIFIX SLEEVE

DO YOU REQUIRE EASIFIX SLEEVE? YES NO

PRECAST EASIFIX

TICK IF YOU REQUIRE ALTERNATIVE QUOTATION FOR PRECAST EASIFIX

JOINT FINISH (TICK THE OPTION YOUR CLIENT REQUIRES AS A JOINT FINISH)

WHITE GROUT CLEAR SILICON WHITE SILICON NOTE : PRECAST EASIFIX PANELS ARE ONLY FINISHED IN WHITE GROUT.

SAFEWALL (COMPLETE AS REQ'D)

NOTE : FOR BEST INTEGRAL STRENGTH, GLASS BLOCK PANELS SHOULD BE INSTALLED INTO A FOUR-SIDED OPENING.

END POSTS

NO. OF POSTS REQ'D : FINISH : WHITE SILVER GREY END BOSS : POLISHED BRUSHED SATIN

CORNER POSTS

A PAIR OF BOSS SECTIONS IS REQUIRED PER POST USED

NO. OF POSTS REQ'D : FINISH : WHITE SILVER GREY CORNER BOSS : POLISHED BRUSHED SATIN

SPECIAL CIRCUMSTANCES/COMMENTS

DESPATCH DETAILS PLEASE STATE DELIVERY ADDRESS IF DIFFERENT FROM ABOVE:

SPECIFY DELIVERY SERVICE (TICK AS REQUIRED) : 3 TO 5 DAY ECONOMY OVERNIGHT

OVERNIGHT CARRIAGE IS SUBJECT TO A SURCHARGE.

DRAWINGS

Sketch layout as required :